



Project/Job Name:

Location:

Fixture Type:

Notes:

65-1010 - LED Linear High-Bay With Interchangeable Lens; 65W/75W/85W Wattage Selectable; 3K/4K/5K CCT Selectable

- Wattage Selectable
- CCT Selectable

Has Driver











ELECTRICAL

| Technology: | LED |
|----------------------------|---------------------------------|
| Watts: | 65W/75W/85W |
| Volts: | 120V-277V |
| Lumens: | 9474L-12739L |
| Lamp Base : | Integrated |
| Lamp Shape : | Integrated LED |
| CRI: | 80 |
| CCT (Kelvins): | 3000K/4000K/5000K |
| Color Description: | Soft White to Natural Light |
| Beam Spread : | 90x90 |
| Hours Rated: | 50000 |
| Dimmable: | Yes-Dimmable |
| DimmableText: | 0-10V Dimming |
| HID Equivalent : | 200W |
| Operating Temperature : | -40C (-40F) to +55C (+131F) |
| Lamp Included : | Integrated |
| Replaceable Light Source : | No |
| Number of LEDs : | 312 |
| Surge Protection : | Built-in surge protection - 6KV |
| THD: | <20% |
| Power Factor : | >0.9 |
| Voltage Type: | Range Voltage |
| Warranty: | 5 Year Limited - Fixtures |
| · | <u> </u> |

PHYSICAL

| Finish: | White |
|----------------|---------------------------|
| Lens Material: | Polycarbonate (PC) |
| Finish Family: | White |
| Dimensions: | L:14.17" W:11.02" H:1.77" |
| Weight (Lbs.): | 5.07 |
| Material: | Die-cast Aluminum |

COMPLIANCE

| Safety Listing: | cULus - Certified |
|---------------------|---------------------------|
| Location Rating: | Damp |
| DLC Approved: | Yes |
| DLC Classification: | Premium |
| DLC ID: | S-56LRO2 |
| DLC Primary Use: | High-Bay Luminaires for |
| | Commercial and Industrial |
| | Buildings |
| CA Prop 65: | Lead |
| BAA Compliant: | No |
| FCC Compliant: | Yes |
| IP Rating: | IP20 |
| RoHS Compliant: | Yes |
| Restrictions: | No Restrictions |

PACKAGING

| Each UPC: | 045923657276 |
|------------------|----------------------|
| Each Quantity: | 1 |
| Each Dimensions: | 14.96 x 11.81 x 2.95 |
| Case UPC: | 10045923657273 |
| Case Quantity: | 1 |
| Case Dimensions: | 14.96 x 11.81 x 2.95 |

INFO

| Includes: | 41 Inch Suspension Kit |
|-----------|------------------------|
|-----------|------------------------|



65-1010 - LED Linear High-Bay With Interchangeable Lens; 65W/75W/85W Wattage Selectable; 3K/4K/5K CCT Selectable

DIMMER COMPATIBILITY

| Legrand | ADPD4FBL3P2W4 |
|---------|---------------------------------|
| Legrand | CD4FBLW |
| Eaton | DF10P |
| | |
| Leviton | DS710-10Z |
| Lutron | DVSCSTV |
| Lutron | DVSTV |
| Leviton | IP710-LFZ |
| Lutron | MS-Z101 |
| Lutron | MS-Z101-V |
| Lutron | NFTV |
| Lutron | NTSTV-DV |
| Legrand | RH4FBL3PTCCCV6 |
| Lutron | RMJS-8T-DV-B + PJ2-3BRL-GWH-L01 |